

CONNECTING

People with Places + Things

IoT Monitoring + Control:

Smart Cities, Security, Environmental, Tower, Fuel, Generator, Power + More!

Ask About Our New Option for
Software Management, VantEdge™



Some things can't be monitored,
for everything else, there's Westell!



Scan to Learn More
About Westell's
Remote Monitoring
Solutions



We specialize in industrial IoT monitoring that delivers intelligence at the edge.

Manage edge devices (new or legacy) and monitor key performance indicators at your site via sensors for both wired and wireless applications.

IOT:
How You Really Connect
RMX-4000

14 Ethernet & PoE

2 Sitebus

4 Selectable Serial

Wireless Sensors

2 GigE SFP

32 Alarm Inputs

2 Analog

Environmental Alarms

Power Metering

Voltage Metering

Remote Terminal Unit

Copper, Fiber, SFP

Temperature & Humidity

Gen Start / Stop

Generator

ATS

Microwave

RRH

Camera

HVAC

Power Plant

Hardware to fit your form factor and budget:



| Feature | RMX-4000 | DMX | RMC-700 | RMM-310 | RMM-400 |
|--------------------------|---|----------------------------------|---------------------------------|----------------------------------|---------------------------|
| SFP | 2 (fiber or copper) | 0 | 0 | 0 | 0 |
| Ethernet | 14 (2GE + 12FE) | 2 (GE) | 2 | 2 | 2 |
| POE Support | 4 | 1 (in), 1 (out) | 0 | 0 | 0 |
| Serial (async) | 4 | 3 | 2 | 0 | 0 |
| Console | USB | BLE or local access via Ethernet | local access via Ethernet | BLE or local access via Ethernet | local access via Ethernet |
| Discrete Inputs | 32 | 8 | 12 | 40 | 128 |
| Analog Inputs | 2 | External Expansion | 1 | 0 | 0 |
| Control Outputs | External Expansion (A90-SBRELAY2) | External Expansion | 1 | 0 | 0 |
| SiteBus | 2 | 1 | 1 | 1 | 1 |
| Built In Sensors | Power Input A & B plus Aux. Battery 0-60V | Power Input A & B | Power Input A & B | - | - |
| 5 VDC Output | 1 | - | - | - | - |
| 24 VDC Output | 1 | - | - | - | - |
| Voltage | 20-60 VDC | 20-60 VDC | 20-60 VDC | 20-60 VDC | 20-60 VDC |
| Expansion | RMB, RME, RMM-300/310 | RMB, RMM-3XX | NO POE | Add RMX, RMC, DMX | Add RMX, RMC, DMX |
| Power Input | Dual A/B +/-20-60VDC | Dual A/B +/-20-60VDC | Dual A/B +/-20-60VDC | Dual A/B +/-20-60VDC | Dual A/B +/-20-60VDC |
| Localized User Interface | SSH, SFTP & HTTPS | SSH, SFTP & HTTPS | SSH, SFTP & HTTPS | HTTPS | HTTPS |
| SNMP Manageable | Yes | Yes | Yes | Yes | Yes |
| WAN Options | LTE Wireless, Ethernet, Fiber SFP | LTE Wireless, Ethernet | LTE Wireless, Ethernet | Ethernet | Ethernet |
| Dimensions, (H, W, D) | 1.75" x 16.86" x 10" | 1.73" x 17" x 5.33" | 5.6" x 9.95" x 0.92" | 1.73" x 17" x 1.2" | 4.6" x 8" x 5.5" |
| Mounting | 19", 21" or 23" Rack | DIN, Rack, Wall, NEMA Enclosure | DIN, Rack, Wall, NEMA Enclosure | Rack or Wall | Rack |
| Internal Clock | Yes | Yes | Yes | Yes | No |



WESTELL

WESTELL.COM