

CONNECTING

People with Places + Things

IoT Monitoring + Control:

Smart Cities, Security, Environmental, Tower, Fuel, Generator, Power + More!

Ask About Our New Option for
Software Management, VantEdge™



Some things can't be monitored,
for everything else, there's Westell!



Scan to Learn More
About Westell's
Remote Monitoring
Solutions



We specialize in industrial IoT monitoring that delivers intelligence at the edge.

Manage edge devices (new or legacy) and monitor key performance indicators at your site via sensors for both wired and wireless applications.

IOT:
How You Really Connect
RMX-4000

14 Ethernet & PoE

2 Sitebus

4 Selectable Serial

Wireless Sensors

2 GigE SFP

32 Alarm Inputs
Multi Door Entry • Smoke/Fire Water • Tower Light • ATS • Gas Motion • Generator • Power

2 Analog

Voltage Metering

Power Metering

Environmental Alarms

Remote Terminal Unit

Copper, Fiber, SFP

Generator

Temperature & Humidity

Gen Start / Stop

ATS

RRH

Camera

Microwave

HVAC

Power Plant

Hardware to fit your form factor and budget:



Feature	RMX-4000	DMX	RMC-700	RMM-310	EdgeLink
SFP	2 (fiber or copper)	0	0	0	1 (some models)
Ethernet	14 (2GE + 12FE)	2 (GE)	2	2	1
POE Support	4	1 (in), 1 (out)	0	0	0
Serial (async)	4	3	1	0	1
Console	USB	BLE or local access via Ethernet	local access via Ethernet	BLE or local access via Ethernet	BLE
Discrete Inputs	32	8	12	40	8
Analog Inputs	2	External Expansion	1	External Expansion	External Expansion
Control Outputs	External Expansion (A90-SBRELAY2)	External Expansion	1	0	0
SiteBus	2 (up to 8 sensors)	1 (up to 4 sensors)	1 (up to 4 sensors)	1	1
Built In Sensors	Power Input A & B plus Aux. Battery 0-60V	Power Input A & B	Power Input A & B	BLE	BLE
5 VDC Output	1	Sitebus Interface	Sitebus Interface	-	Sitebus Interface
24 VDC Output	1	-	-	-	-
Voltage	20-60 VDC	20-60 VDC	20-60 VDC	20-60 VDC	100-267VAC
Expansion	RMB, RME, RMM-300/310	RMB, RMM-3XX	NO POE (Expand with RMB or RMM-3XX)	Add RMX, RMC, DMX	n/a
Power Input	Dual A/B +/-20-60VDC	Dual A/B +/-20-60VDC	Dual A/B +/-20-60VDC	Dual A/B +/-20-60VDC	50 or 60H
Localized User Interface	SSH, SFTP & HTTPS	SSH, SFTP & HTTPS	SSH, SFTP & HTTPS	SSH, SFTP & HTTPS	HTTPS
SNMP Manageable	Yes	Yes	Yes	Yes	MQTT
WAN Options	LTE Wireless, Ethernet, Fiber SFP	LTE Wireless, Ethernet	LTE Wireless, Ethernet	Ethernet	LTE Wireless, Ethernet, Fiber SFP
Dimensions, (H, W, D)	1.75" x 16.86" x 10"	1.73" x 17" x 5.33"	5.6" x 9.95" x 0.92"	1.73" X 17" X 1.2"	10" x 7.1" W x 3"
Mounting	19", 21" or 23" Rack	DIN, Rack, Wall, NEMA Enclosure	DIN, Rack, Wall, NEMA Enclosure	Rack or Wall	Pole or wall
Internal Clock	Yes	Yes	Yes	Yes	No



WESTELL

WESTELL.COM