

## Benefits



Precision position, heading, heave, pitch and roll in a single compact unit

All systems are GPS, GLONASS, and BeiDou capable for position and heading seeding

Improved heading lock stabilization

Built-in NTRIP Client

Maximum performance and accuracy under conditions of poor GNSS reception

Adherence to International Hydrographic Organization (IHO) survey standards  
F280 Series directly supported in leading Hydrographic Survey applications

Reduced installation time

Applicable for slow or non-moving platforms through use of Pre-calibrated Housing

Easy to use Web Interface

Highly Competitive Price

Expert 24x7 Technical Support

Waterproof housing rated to IP67 standards

## Accurate, reliable MOTION and positioning data in a compact ruggedized IP67 Rated Housing

**The F290 GNSS-aided (inertial) attitude and positioning systems are high quality, robust packages for the marine hydrographic and laser survey market. This new generation of GNSS-Aided INS systems embeds high accuracy components (accelerometers and gyros) and smart algorithms.**

Defined to meet the exacting requirements of the multibeam survey market, the F290 systems are easy to install, easy to use and produce very accurate positioning, heading and MOTION data in the most dynamic offshore conditions.

Includes built-in NTRIP Client that allows receiving GNSS RTK quality GNSS Corrections over the internet without need of any PC. F280 Series® must be connected to Ethernet network with Internet access and a separate NTRIP subscription.

The light yet rugged F290 is a reliable and cost-effective solution on marine survey vessels of all sizes. All systems are GPS, GLONASS, and BeiDou enabled to improve constellation coverage and heading lock stabilization.

Easy-to-use web interface provides configuration, control and processing functionality including iHeave (intelligent heave).

In addition to real-time heave measurement and output, the F290 now directly computes and outputs our long-standing and proven iHeave (intelligent Heave) solution without the need for top-side processing or software. iHeave is a tailored solution specifically for long period ocean swell compensation and is fully integrated with the F290 Precision Attitude and Positioning Systems. In many parts of the world, hydrographic survey is severely affected by low frequency ocean swells often up to 70 seconds long, resulting in distortions in bathymetric measurements. Conventional techniques for real-time heave measurement can only offer limited accuracy and are insensitive to ocean swells exceeding 10 to 20 seconds. The inbuilt iHeave algorithm analyzes the raw motion data and allows a more accurate determination of the real heave motion experienced by a vessel, and enables the output of precise heave values for all ocean swells.

Additionally, for extremely rapid vessel deployments, a Pre-Calibrated Housing accessory is available to significantly reduce the installation and calibration phases of operation.

## Features

- Survey grade GNSS, attitude and heave sensor in one box
- With addition of integrated Atlas corrections receiver and Atlas H10 Global Correction Service License (L-Band). (Yearly Subscription for Atlas Service required.)
- High accuracy position, heading, heave, pitch and roll at up to 100 Hz
- Built-in NTRIP Client capable of receiving GNSS Corrections over Internet.
- Connectivity to multiple sensors simultaneously over Ethernet and Serial
- Multiple lever arms to support precise INS positioning for multiple platform locations or sensors
- Explicit vessel Centre of Gravity (COG) support for improved heave accuracy
- Rapid Heading initialization (Under 30 secs typically)
- Web based setup and monitoring - ability to store multiple different profiles and recall these instantly - ideal for survey teams with multiple vessels
- Tightly integrated GNSS and inertial components result in increased accuracy and reduced setting times when compared to outputs from separate sensors
- Enhanced performance under conditions of poor GNSS reception
- Compatible with HYPACK, QINSY, CARIS and other navigation packages
- Industry standard formats and interfaces
- iHeave (intelligent Heave) processing available as standard

## Applications

- Hydrographic Survey
- Bridge, dam, harbour inspection
- Dredging
- Offshore renewable energy
- Environmental survey
- Shipping channel survey
- Marine laser scan survey

## F290

F290 The F290 is Multi Frequency multi GNSS system with Atlas H10, RTK, DGPS and SBAS GNSS corrections capabilities (1cm positional accuracy). There are other models within F280 Series® of GNSS-Aided INS Systems (Yearly subscription required).

All systems are GPS, GLONASS, and BeiDou capable for position and heading seeding

Models within F280 Series® are field-upgradable. Pre-calibrated housing upgrades can be applied to any model.

## Dynamic Positioning

## Physical

Positional Accuracy (RMS)	0.04m with Atlas Global Correction Service 0.008m + 1ppm with L1/L2 RTK Correction 0.30m with DGPS correction 0.30m with SBAS correction 1.20m no correction	Dimensions	127mm x 155mm x 113mm (5in x 6.1in x 4.4in)
Roll and Pitch (1σ)	0.02°	Weight	2.2kg (4.9 lbs)
True Heading (1σ)	0.04° (2m baseline) 0.025° (4m baseline)	Power	9-36Vdc, 15 Watts (110-240Vac adapter supplied)
Heave (1σ)	5cm or 5% (on-line) 3.5cm or 3.5% (iHeave)	Power and Data Cable	5m standard, or 20m, or 50m optional (16.40ft standard, or 65.62ft or 164.04ft optional)
Velocity (1σ)	0.014 m/s	Antennas	Multi-Frequency, Multi-GNSS, SBAS and Atlas corrections capable
		Antenna Cables	15m (49.2ft) standard 30m (98.4ft) optional
		Operating Temperature	-10° to 60° C (14° to 140°F)
		Waterproof	IP67 Rated Maximum depth of 1 meter up to 30 minutes. When Power and Antenna connectors are mated
		Vibration	0.1g <sup>2</sup> /Hz, 5-500 Hz

## Interfaces

Ethernet 100Mbit	Full control and configuration, high speed data output (COMPAC), NTRIP corrections User-configurable for position, heading and attitude strings. Choose from: TSS1, TSSHHRP, EM1000, EM3000, COMPAC, GGA, GSA, GST, GSV, GGK, HDT, PASHR, PRDID, PTCF, RMC, ROT, VTG, UTC, ZDA, PPS and SPD.
Serial Port 1	User-configurable for position, heading and attitude strings. Choose from: TSS1, TSSHHRP, EM1000, EM3000, COMPAC, GGA, GSA, GST, GSV, GGK, HDT, PASHR, PRDID, PTCF, RMC, ROT, VTG, UTC, ZDA, PPS and SPD.
Serial Port 2 & 3	As Serial Port 1
GNSS Correction Port	Correction input (DGPS, RTK) Formats: RTCM 2.1/2.2/2.3/3.0/3.1; CMR, CMR+
Other	1 PPS on BNC

## PC System Requirements

Web Interface Compatible with all major browsers.

Copyright© 2026 Coda Octopus

F280® (Reg, Us Pat & TM off), F285, F290, iHeaveTM & INSightTM are trademarks of Coda Octopus. HYPACK® is a registered trademark of HYPACK, Inc. Windows® is a registered trademark of Microsoft®. CARIS® is a registered trademark of CARIS. Atlas™ Global Correction Service and AtlasLink™ are trademarks of Hemisphere.

The information in this publication was correct when it was published but specifications may change without notice. Photos are included for illustrative purposes only and actual items may differ in appearance. Coda Octopus does not assume responsibility for typographical or photographic errors. Issue 01.2026

Sales Worldwide: +44 131 553 1380 Sales Americas: +1 407 735 2400

More Information: sales@codaoctopus.com salesamericas@codaoctopus.com www.codaoctopus.com

Technical Support Worldwide: +44 131 553 7003 Technical Support Americas: +1 888 340 2632