

# CREATE TOUGH BONDS THAT LOOK GREAT

**ARALDITE® 2031-1 adhesive gives you the power to create tough, yet elegant products.**

ARALDITE® 2031-1 adhesive provides the balance of finesse and toughness that you need to create high-performance products with standout aesthetics. Offering superior resistance to dynamic loads, along with high fracture toughness, this well-proven adhesive is suited for use on sports cars, racing boats and bicycles.

Black in color, ARALDITE® 2031-1 adhesive allows you to create invisible bond lines on carbon composites, with spacers to ensure a minimum bond line thickness of 0.05 mm. The adhesive provides resistance to weathering and high lap shear strength for use on products in demanding outdoor conditions, such as wind turbine blades.

## PRODUCT BENEFITS

- Black color to match carbon composites
- Room temperature curing
- Resistant to weathering and dynamic loading



**MADE POSSIBLE**

**CREATE ELEGANT YET TOUGH COMPOSITE APPLICATIONS WITH INVISIBLE BOND LINES.**



ARALDITE® 2031-1 adhesive is a black adhesive specifically designed to bond advanced composites with high strength.

**SUPERIOR PERFORMANCE**

**60 mins**  
60-min pot life at room temperature

<b>2C</b> Epoxy technology	<b>145,038 psi</b> Tensile modulus
<b>3,335 psi</b> Tensile strength	<b>ca. 12%</b> Elongation at break

**212°F**  
212°F maximum continuous operating temperature\*

**3 hrs**  
3-hr fixture time at room temperature

**↑ 10 mm**  
Gap-filling up to 10 mm

\* For the maximum continuous operating temperature, we consider the maximum temperature for which the residual lap shear strength is 1/3 of the lap shear strength at room temperature or the temperature for which the residual lap shear strength is 725 psi.

With our Material Models, you get fast and accurate simulations when qualifying adhesives for your project.

**Click to find your Material Model**



**Legal information**

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. or Huntsman Advanced Materials (Guangdong) Ltd. ("Huntsman"). The following supersedes Buyer's documents. While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/or lab work. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights. The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and in direct customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product. Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

ARALDITE® is a trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.  
© 2020 Huntsman Corporation. All rights reserved.  
Ref. No. AdMat\_Araldite 2011\_core range\_EN\_EU\_June 2021

**Americas**

Huntsman Advanced Materials Americas Inc.  
10003 Woodloch Forest Drive  
The Woodlands, TX 77380, USA  
Tel.: +1 888 564 9318  
Fax: +1 281 719 4047



BPA free

**Asia Pacific**

Huntsman Advanced Materials (Guangdong) Co., Ltd,  
Shanghai Branch Office  
455 Wenjing Road, Minhang District  
Shanghai 200245, P.R. China  
Tel: +86 21 3357 6588  
Fax: +86 21 3357 6547

**Europe, Middle East & Africa**

Huntsman Advanced Materials (Switzerland) GmbH  
Klybeckstrasse 200  
P.O. Box  
4002 Basel, Switzerland  
Tel.: +41 61 299 1111  
Fax: +41 61 299 1112

For more information: [www.huntsman.com](http://www.huntsman.com)