

Neo Nanobubble Generator



APPLICATIONS

- Deep Water Culture
- NFT
- Drip Irrigation
- Water Tank Oxygenation
- Reservoir Oxygenation
- Algae Control
- Biofilm Control*

The patented Moleaer Neo Nanobubble Generator is a highly efficient gas-to-liquid injection technology that converts bulk oxygen into nanobubbles and supersaturates water with high levels of dissolved oxygen (DO). Negatively charged, neutrally buoyant nanobubbles remain suspended in water for long periods of time, acting like an oxygen battery that delivers oxygen to the entire body of water. As oxygen is consumed, the nanobubbles continue to diffuse more oxygen into solution to maintain optimal levels of DO. The nanobubbles produce a natural oxidant capable of reducing biofilm growth* and suppressing harmful pathogens, even in warm water. Moleaer's Neo is an economical and highly effective tool that improves water quality, suppresses root disease and promotes the growth of healthy, resilient plants.

The Neo comes with an energy efficient industrial-grade Lowara pump with an open impeller and a PLC controller that enables automation and control of the Neo when not used in continuous operation. The system is quiet and corrosion-resistant with stainless steel components. The Neo comes standard with an integrated low maintenance, optical DO sensor for real time monitoring. Available 34 and 57 m³/hr flow rates, the Neo is designed for durable operation and easy installation into existing irrigation or water treatment system.

FEATURES & BENEFITS

- <200 nm-sized bubbles produced in excess of 1 billion nanobubbles / mL
- Improved water quality
- Oxygenation of any tank and any depth of water
- Enhanced or optimized nutrient absorption in plants
- Promotion of beneficial bacteria, suppression of pathogens
- Easy integration with fertigation and climate control systems
- Auto gas shut off if loss of prime feed
- Low feed gas pressure sensor and alarm
- Integrated real-time DO monitoring
- Corrosion resistant stainless-steel frame and components

*Organic, bio-based nutrients may impact biofilm accumulation rates.

www.moleaer.com

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. Moleaer assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. Copyright © 2020 Moleaer. All trademarks stated herein are the property of their respective company. All rights reserved. This document is confidential and contains proprietary information of Moleaer Inc. Neither this document nor any of the information contained herein may be reproduced, redistributed or disclosed under any circumstances without the express written permission of Moleaer Inc.

Models	NEO 150 Standard	NEO 250 Standard
Liquid Flow Capacity (water)		
Flow Rate, m ³ /hr	34	57
Maximum Liquid Pressure, Bar		1.5
Operating Parameters		
Temperature Tolerance, °C		50-60
Solids, mm		<9.5
Gas Feed		
Maximum Gas Pressure, Bar		8.5
Indicated Gas Flow Range, L/Min	0 - 10	0 - 14
Electrical Power		
Voltage	400	400
Phase	3	3
Hz	50	50
Total KW	2.2	4
Total Amp Draw	5.5	10.0
Pump		
Pump Type	TEFC	TEFC
Wetted Parts Materials	Buna-N/316 SS	Buna-N/316 SS
Controls		
Power (Light)	On/Off DP	On/Off DP
Motor Starter	400v IN to 24 VDC OUT w/OL protection	400v IN to 24 VDC OUT w/OL protection
Start Switch	On/Off (24V DC)	On/Off (24V DC)
Dissolved Oxygen (DO) Sensor ¹	Optical, 0 - 50 ppm (+/- 1.5 ppm), 0-5 mV	Optical, 0 - 50 ppm (+/- 1.5 ppm), 0-5 mV
Connections		
Customer Pipe Connection, mm	75	90
Inlet, mm	75	90
Discharge, mm	90	90
Gas Fitting for External O ₂ ²	1/4" BSPTF	1/4" BSPTF
Dimensions and Weight		
Height, cm	107	107
Width, cm	68	68
Length, cm	107	107
Weight, kg	100	162

Note 1: Indicated gas flow range represented under pressure and not represented under standard conditions.

Note 2: When using oxygen, Moleaer recommends CGA inlet 540, outlet 9/16" - 18RH pressure regulator with delivery range of 0.34-10.3 bar.