

**Fourth Generation of Echoscope<sup>®</sup> Sonars**

- Lighter/Smaller/Less Power Requirements
- More Versatile Deployments Possible
- Shallow Water Depth Rating
- Designed for small USV installation

**Benefits**

- Improved situational awareness
- Highest definition of multibeam data output in the world
- Real time decision making
- Increased productivity
- Maintain subsea operations in zero visibility
- Enhanced safety
- Expert 24x7 Technical Support



**20m Depth Rating**

**The Echoscope<sup>4G</sup> C-Series. Compact real-time 3D sonar for performance and economy**

The new Echoscope<sup>4G</sup> C500 Surface is the latest Surface variant of our 4<sup>th</sup> generation real-time 3D imaging sonar platform. Designed specifically with small USV use in mind, the Echoscope<sup>4G</sup> C500 Surface builds on the advantages of our Compact range by offering the lightest, smallest and easiest to integrate real-time 3D sonar on the market today.

The 4G platform is delivered in a smaller, lighter housing which will for the first time give customers with smaller USVs the opportunity to integrate a real-time 3D imaging and mapping sonar. With the sonar's unique capability to generate real-time 3D images around complex structures, this will enable inshore security inspection, asset integrity mapping and search and rescue operations to be quickly and effectively undertaken from the smallest of available platforms.

In common with all of our real-time 3D sonars, the C500 Surface generates a complete 3D model composed of over 8,000 soundings from each and every acoustic transmission. This 3D model is entirely refreshed up to 20 times per second with each new transmission.

The Echoscope<sup>4G</sup> C500 offers two different models with a wide range of flexible applications:

	Frequency	Angular Coverage
<b>Dual Frequency</b>	375,630kHz	50°x50°, 24°x24°
<b>Triple Frequency</b>	240,375,630kHz	90°x44°, 50°x50°, 24°x24°

With sounding densities far in excess of those generated by other sonars, combined with the new increased 20Hz ping rate, the C500 presents unrivalled clarity of dynamic operations and moving objects in video-like data format in all water conditions including low visibility water conditions. All the Echoscope<sup>4G</sup> range take advantage of patented statistical rendering techniques to further enhance the clarity of the image, presenting the user with an intuitive and easy-to-interpret image.

In mapping and inspection tasks, the ping geometry of the C500 will allow a target to be visualized many times in a single pass, with each view taken from a different angle. This allows complex subsea structures to be mapped with a level of confidence and detail for beyond anything than can be achieved using alternative methods.

Whether deployed on inland waterway works or large scale offshore projects, the Echoscope<sup>4G</sup> C500 Surface real-time 3D sonar will provide clear imagery of the underwater environment.

**New Features**

- Lighter/Smaller/Reduced Power Requirements
- Increased ping rate now 20Hz
- Reduced minimum range now 0.5m
- Programmable TVG
- Standard 100mb Ethernet for ROV/AUV applications

Technical Specifications		
Performance (by Model)	Dual Frequency	Triple Frequency
Frequency	375 and 630kHz	240/375 and 630kHz
Number of beams	128 x 64 (8,192 total)	128 x 64 (8,192 total)
Maximum range**	120m (394ft) at 375kHz 80m (262 ft ) at 630kHz	150m (492ft) at 240kHz 120m (394ft) at 375kHz 80m (262 ft) at 630kHz
Minimum range	0.5m (1.64ft)	0.5m (1.64ft)
Range resolution	3cm (1.2in)*	3cm (1.2in)*
Update rate (ping rate)	Up to 20 Hz software selectable	Up to 20 Hz software selectable
Angular coverage	50°x50°, 24°x24°	90°x44°, 50°x50°, 24°x24°
Beam spacing	375kHz: 0.39°x0.78° 630kHz: 0.19°x0.38°	240kHz: 0.70°x0.69° 375kHz: 0.39°x0.78° 630kHz: 0.19°x0.38°
*Software selectable **The actual working range will depend on the target's size, reflectivity, and the level of detail required for the application		
Physical		
Dimensions (h x w x d) (excluding connectors)	232mm x 301mm x 126mm (9.1in x 11.8in x 5.0in)	265mm x 301mm x 137mm (10.4in x 11.8in x 5.4in)
Dimensions (h x w x d) (including Echoscope® Protective Cover)	242mm x 311mm x 129mm (9.5in x 12.2in x 5.1in)	270mm x 311mm x 160mm (10.6in x 12.2in x 6.3in)
Weight in Air	10.8kg (23.8 lbs)	11.2kg (24.7 lbs)
Weight in Water	3.25 kg (7.2 lbs)	3.6kg (7.9 lbs)
Power Consumption	2-6A at 24Vdc	2-6A at 24Vdc
Depth Rating	40m (131ft) <i>Failure to keep within this depth rating can irretrievably damage the unit.</i>	40m (131ft) <i>Failure to keep within this depth rating can irretrievably damage the unit.</i>
Interfaces		
Sonar head to PSU	Power: 24V DC Control: RS232 Serial Cable Data: 100Mb Industry Standard Ethernet Single cable for power, data and control	Power: 24V DC Control: RS232 Serial Cable Data: 100Mb Industry Standard Ethernet Single cable for power, data and control

### Echoscope® Features

- 🌀 High definition 3D sonar image generated in real-time
- 🌀 Mosaicking capability
- 🌀 Displays complex moving structures accurately
- 🌀 Accurate even in turbid water
- 🌀 Accurate geo-referenced data
- 🌀 Versatile DTM output options
- 🌀 Very easy to use even by non sonar experts such as crane operators and law enforcement officers

### Echoscope<sup>4G</sup> Protective Cover Included

The Echoscope<sup>4G</sup> C500 Surface sonar is supplied with a replaceable encapsulating cover for the sonar head, protecting the hard-anodized aluminium housing from light impact, scratching and marine fouling. The protective cover can be removed for general cleaning of the unit and removal of any marine fouling from the cover. Made from Derlin™, the cover is a lightweight, easy to install protection accessory.

Copyright© 2020 Coda Octopus  
CodaOctopus®, Echoscope®, Echoscope4G®, Echoscope® PIPE, Echoscope4G® PIPE, Echoscope® 6D, Echoscope® 5D, 5D Echoscope® 4G USE® Ping-Pong Echoscope® Sonar, Ping-Pong® Sonar, Ping-Pong Echoscope® are trademarks of Coda Octopus. This list is not exhaustive of all our trademarks used with our products and/or services.

The information in this publication was correct when it was published but specifications may change without notice. Photos are included for illustrative purposes only and actual items may differ in appearance. Coda Octopus does not assume responsibility for typographical or photographic errors. Issue 1.7 (6.21)

Sales Worldwide: +44 131 553 1380      Sales Americas: +1 407 735 2400  
More Information: sales@codaoctopus.com      salesamericas@codaoctopus.com      www.codaoctopus.com  
Technical Support Worldwide: +44 131 553 7003      Technical Support Americas: +1 888 340 2632

