

Construction Monitoring Solution (CMS)

A Patented Solution

A Patented and Complete Breakwater Construction Management System to See, Track, Place, Monitor, Validate and Document Concrete Armored Block Placement.

CMS is a full life-cycle Construction Management System for breakwater projects, CMS supports everything from design through construction, maintenance, and inspection. Using patented real-time 3D technology, it enables teams to see, track, place, monitor, and validate block installation while capturing settlement movement. The platform delivers a high-fidelity digital twin, providing engineers with accurate, actionable data throughout the project lifecycle.



Key capabilities include:



See, Track, Place, Record and Document Blocks as Laid

The acoustic point cloud data of each block is recognized by the software, a 3D model of the block selected by the operator and the solution automatically locks the model onto the point cloud data. The operator has a clear 3D model of the block to work from, enabling increased accuracy of block lay, as the operator can 'see' all sides of the block



Construction Workflow Management

CMS provides the capability to manage, monitor and document the entire construction phase of asset placement projects. Site design, prelay information, and data can be loaded into CMS (full X,Y,Z positions and rotations) for control, progress reporting and full-time visualization of placed assets, including those being actively placed



Real-Time Visualization

Real-time 3D visualization of blocks and slope irrespective of water conditions for increased productivity, diver-less placement and pre/post-lay survey



3D Automatic Tracking

The unique model tracking technology means the final position and attitude can be recorded in the global CMS database. The tracking can be further activated on subsequent survey data allowing the master asset database to be quickly updated with any block-placement movement

Construction Monitoring Solution (CMS) History


CMS is the leading, industry-proven solution, developed in collaboration with prominent marine engineering firms since 2008. It is formally approved by armour unit manufacturers who define breakwater design specifications. CMS is used on many major breakwater projects worldwide, many of which run over multi-years, supporting both the pre-and post-lay surveys across all standard single-layer concrete armour block types.

The CMS solution integrates with our Echoscope PIPE® real-time 3D sonar systems and our latest Echoscope® AIR LiDAR 2.0 real-time 3D sensor to deliver seamless, real-time visualization above and below water. This enables continuous tracking of moving blocks at all stages of construction, in all water conditions and day or night visibility.

In addition to the critical real-time visualization for crane operators, the system can provide precise measurement of block position and orientation, and supports accurate placement, and records verified as-laid data, delivering survey-grade results in full compliance with project engineering requirements.

Unlike traditional breakwater construction approaches, which often require separate technologies for placement, slope and placement survey, CMS enables the entire workflow steps to be performed on demand, using the same equipment, eliminating the need for survey vessels or additional sensors.

Because the solution provides a seamless and dynamic work-flow and allows the operator to see the blocks in real time 3D, this significantly reduces the time it takes to place the blocks and increases the safety of those involved in the block placement process. Users of our CMS Solution obtain significant productivity gains, increasing the number of blocks placed to anywhere between 76-200 blocks per day, while at the same time increasing safety.



ZADCO SLEEPER PLACEMENT

WAS

4 Sleepers Placed
in 12 Hours

NOW


76 Sleepers Placed
in 24 Hour Shifts

>3000%
Productivity

>\$3 Million
Cost Savings

3-6 Months
Duration

Our patented Block Tracking technology creates significant benefit throughout multiple stages in the breakwater construction process. Block Tracking can be employed for the live placement of the blocks, Block Detection post-lay as the panel is built, capturing settlement of the block and finally Block Detection of the entire panel and breakwater from final as-laid survey data.



CMS generates industry standard deliverables for breakwaters and extends to the full scope breakwater construction from:



VISUALIZATION OF BLOCK

ACCURATE BLOCK POSITION

MAINTAIN MINIMUM SEPARATION
BETWEEN BLOCKS

MAINTAIN MINIMUM PACKING DENSITY
OF BLOCKS

QUALITY CONTROL OF EACH BLOCK
POST-LAY POSITION



3D MAP OF COMPLETE BREAKWATER

XYZ POSITION OF EACH BLOCK

PRE- AND POST-LAY SURVEYS

DETECT BLOCKS MOVED FROM
POSITION

QUALITY CONTROL OF EACH PANEL/
COMPLETE CONSTRUCTION

Using CMS enables precise tracking and recording of block position and orientation throughout placement, post-lay analysis, and final survey data collection—without the need for additional sensors.

The system provides real-time 3D underwater scene awareness for crane operators, supporting continuous 24/7 operations regardless of water visibility. This improves placement accuracy, increases productivity, and enhances confidence in the final resting position of each block.

By improving operational visibility, CMS also enhances diver safety and reduces reliance on divers during installation. In addition, it supports real-time, survey-grade slope inspection before, during, and after placement, as well as full post-lay surveys of completed panels—all using the same equipment.

The platform is adaptable for both wire cranes and excavators, enabling flexible deployment across a wide range of project configurations.



	Visualization Only	Visualization & Mapping Solution
		
Block Imaging - Assist in Placing Blocks	✓	✓
Relative Measurements	✓	✓
Assess Interlocking Blocks	✓	✓
Quality Check Slope Prior to Block Lay	✓	✓
Planned Block Positions	✗	✓
Real-Time Block Tracking	✗	✓
3D Models of Blocks	✗	✓
Database of Laid Blocks	✗	✓
Post-Lay Positioning	✗	✓

CMS supports a number of different block types which are listed below. If your Block Type is not currently listed, please contact us and we can extend our support for your Project Block Type.



ACCROPODE™ I



ACCROPODE™ II



ACCROBERM I



ACCROBERM II



CORE-LOC



Dolos



ECOPEDE



Tetrapods



XBloc®



XBloc® Plus

Equipment Composition (With Positioning & Attitude Data)



Echoscope PIPE® Surface (With In-Built Wet Switch)

The Echoscope PIPE® Surface Models is supplied with an in-built wet switch, and benefit from being much lighter, while maintaining the same High-Resolution 3D Volumetric capabilities offered by the Echoscope PIPE®. Surface variants are rated at 40m water depth, making them ideal for shallow water applications with good water conditions, such as concrete armored block placement.



Integrated Single Axis Rotator (4G ISAR)

The 4G ISAR is a high-performance unit designed to meet the demanding requirements of accurate orientation and position control for real-time 3D Coda Octopus sonar products. All angular and positional offsets are dynamically calculated within the software, ensuring accurate, efficient, and simple operation.



F280® Pre-Calibrated Assembly

The F280® GNSS-aided (inertial) attitude and positioning systems are high quality, robust packages for the marine hydrographic and laser survey market. Defined to meet the exacting requirements of the multibeam survey market, the F280 Series® systems are easy to install, easy to use and produce very accurate positioning, heading and MOTION data in the most dynamic offshore conditions.




Echoscope® AIR LiDAR 2.0

Capable of providing the same real-time 3D volumetric data as the Echoscope PIPE® Series but above the waterline, the Echoscope® AIR LiDAR 2.0 is designed for both mapping and inspection applications, providing seamless above and below water visualization of blocks.



3D Connect 5G & Laptop

Designed to effortlessly handle data and control of all Coda Octopus 3D Hardware while also supporting additional sensors such as Sound Velocity Profilers. The 3D Connect 5G allows users to further simplify deployment of the Echoscope® range of 3D sonars, increasing project efficiency by saving time with an intuitive, easy-to-use solution.



Construction Monitoring Solution (CMS)

Our CMS solution is the leading industry solution, which has been developed in collaboration with prominent engineering firms since 2008 and is approved by the Block Manufacturers who design the breakwater technical specifications.



4G USE®

For use with the Echoscope® range of real-time 3D sonars and our Echoscope® AIR LiDAR 2.0, the Coda Octopus' 4G USE® software will enable you to view the scene above and below the water in the highest definition possible, and has been developed specifically to provide significant productivity and result processing capability.


Equipment Composition (Alternative) Visualization Only

Alternatively Operators can utilize the Echoscope PIPE® for Visualization only, allowing for Block Imaging to assist in Placement of Blocks, Relative Measurements for Precise Placement, Access to Interlocking of Blocks and the Ability to Quality Check the Slope prior to block placement. However without Positioning and Attitude Data, Operators lose access to defining traits of CMS, such as Real-Time Block Tracking, Planned Block Placements and a Database of Laid Blocks.



Echoscope PIPE® Surface (With In-Built Wet Switch)

The Echoscope PIPE® Surface Models is supplied with an in-built wet switch, and benefit from being much lighter, while maintaining the same High-Resolution 3D Volumetric capabilities offered by the Echoscope PIPE®. Surface variants are rated at 40m water depth, making them ideal for shallow water applications with good water conditions, such as concrete armored block placement.



Integrated Single Axis Rotator (4G ISAR)

The 4G ISAR is a high-performance unit designed to meet the demanding requirements of accurate orientation and position control for real-time 3D Coda Octopus sonar products. All angular and positional offsets are dynamically calculated within the software, ensuring accurate, efficient, and simple operation.



Echoscope® AIR LiDAR 2.0

Capable of providing the same real-time 3D volumetric data as the Echoscope PIPE® Series but above the waterline, the Echoscope® AIR LiDAR 2.0 is designed for both mapping and inspection applications, providing seamless above and below water visualization of blocks.



3D Connect 5G & Laptop

Designed to effortlessly handle data and control of all Coda Octopus 3D Hardware while also supporting additional sensors such as Sound Velocity Profilers. The 3D Connect 5G allows users to further simplify deployment of the Echoscope® range of 3D sonars, increasing project efficiency by saving time with an intuitive, easy-to-use solution.



4G USE®

For use with the Echoscope® range of real-time 3D sonars and our Echoscope® AIR LiDAR 2.0, the Coda Octopus' 4G USE® software will enable you to view the scene above and below the water in the highest definition possible, and has been developed specifically to provide significant productivity and result processing capability.

When placing blocks from sea-side, the Echoscope PIPE® can easily be deployed on a barge with a pole-arrangement. The system can be easily deployed on excavator, wire cranes, or mounted on a custom-made frame. The mounting arrangement would be designed by the customer. Coda Octopus will provide assistance through the process, to ensure that the arrangement is suitable to obtain the clearest image of the blocks being placed.

Note: When placing different block sizes, the pitch angle (A) of the Echoscope® and the length of the frame (l) are important.



Common Deployment Methods



Excavator Crane Deployment

This is one of the most common methods of deployment for the CMS solution. The Echoscope® is mounted on a horizontal frame on the placement tool.



Separate Frame

The Echoscope PIPE® is mounted on a separate frame which is suspended from a separate smaller crane. In this case, the block crane is completely independent of the survey frame. The waterproof IMU and the GPS antenna are mounted on the separate frame used to visualize the block crane.



Wire Frame

This deployment is our innovative solution for customers using a wire crane to place blocks. The Echoscope® is mounted on the bottom frame in a similar position to the excavator crane deployment. Then, an 8m pole is connected to the bottom frame to attach a rigid support bar which holds the waterproof GPS and INS mounted on a spreader bar.

Our breakwater solution has been adopted by major operators and is proven to deliver significant productivity gains. Some examples of which are:

ACCROPODE™ Projects

Satah al-Razboot, UAE

ZADCO Upper Zakum oil Fields, UAE

Constanta, Romania

Ras Laffen, Qatar

XBloc

Sumburgh, Scotland

Swinoujscie, Poland

Offshore Island, Abu Dhabi

Dunkerque, France

Others

CORE-LOC®

Tetrapod

Bloque Cubic
Rainure (BCR)

Antifer

Al-Zour, Kuwait

Tokushima, Japan

Port of Safi,
Morocco

Hamifratz Port,
Israel

Common Deployment Methods

Eric Peeters of Van Oord says:

“Van Oord has been using the Echoscope real-time 3D imaging sonar on various projects from 2008 onwards where single-layer artificial armour units (ACCROPODE™ & ACCROPODE™ II) need to be placed. During placement, the Echoscope 3D imaging sonar provides real-time guidance to the crane operator. The Echoscope has contributed to an increased productivity whilst improving safety. Over the last year, Van Oord has taken part in the development of the CMS 2.0 solution which provides, amongst other new features, enhanced ACCROPODE™ tracking functionality which makes it another leap forward to diverless placement. By providing a test location in Constanta, Romania, it was possible to feed the software developers instantly with new information. Van Oord operates around the world as a leading contractor for dredging, marine engineering, and offshore energy projects (oil & gas and offshore wind).



Our CMS software is available to license for fixed periods of 6, 12, 24, or 36 months. Each CMS license is linked to a specific Echoscope® sonar and can only be used with this system. Please contact sales@codaoctopus.com for more information on how to obtain a CMS license.

Processor	Intel® Core™ i7/i9 or AMD Ryzen 7/9 Recommended
RAM (Computer Memory)	Minimum 16 GB Recommended
Disk Space (Software)	100mb for installation Approximately 3 - 3.5 GB per hour, dependant on ping rate
Disk Space (Data Storage)	500GB Minimum - 1TB Recommended Data Storage rate is typically up to 3.5 GB per hour (Dependent on ping rate, UIS Camera and Charts and Model Data loaded)
Graphics (Laptop/Desktop)	NVidia® GeForce RTX 4060 (Desktop) NVidia® RTX 4070 (Laptop) *AMD Radeon™ GPUs are not supported
Operating System	Windows® 11
Ethernet (Live Operations)	1 x 10/100/1000 Port (Recommended) 2 x 10/100/1000 Port (Recommended)
USB 2.0/3.0 Ports	3 Minimum 6 Recommended

US 9,019,795

Method of Object Tracking Using Sonar Images

US 10,088,566

Object Tracking Using Sonar Images

US 8,854,920

Volume Rendering Sonar

US 7,898,902

Method Representation of Sonar Images

Copyright © 2020-2026 Coda Octopus Products Ltd and Coda Octopus Group, Inc.

All rights reserved. No part of this document, including the products and software described in it, may be stored in a retrieval system, transmitted, or reproduced by any means, including, but not limited to photocopy, photograph, digitizing, or otherwise - without the written permission of the publisher.

Echoscope®, Echoscope4G®, Echoscope PIPE®, Echoscope® Ping Pong, Echoscope® 5D, Echoscope® 6D, Ping-Pong Sonar®, Ping-Pong Echoscope®, Echoscope PIPE Nano Gen Series®, 4G USE®, CodaOctopus®, F180 Series®, F280 Series® (Reg, Us Pat & TM off) are trademarks of Coda Octopus. The information in this publication was correct when it was published but specifications may change without notice. Photos are included for illustrative purposes only and actual items may differ in appearance. Coda Octopus does not assume responsibility for typographical or photographic errors.

Other products that are referred to in this document may be either trademarks and/or registered trademarks of the respective owners. The publisher and the author make no claim to these trademarks. Specifications and information contained in this manual are furnished for informational use only, and are subject to change at any time without notice, and should not be construed as a commitment by Coda Octopus Products. Coda Octopus Products assumes no responsibility or liability for any errors or inaccuracies that may appear in this manual, including the products and software described in it. While every precaution has been taken in the preparation of this document, the publisher and the author assume no responsibility for errors or omissions, or for damages resulting from the use of information contained in this document or from the use of programs and source code that may accompany it. In no event shall the publisher and the author be liable for any loss of profit or any other commercial damage caused or alleged to have been caused directly or indirectly by this document.

Special thanks to Concrete Layer Innovations and Delta Marine Consultants for providing the 3D models of the breakwater block types pictured in this document. ACCROPODE™, ACCROPODE™ II, ECOPODE™, ACCROBERM™ I, and ACCROBERM™ II are trademarks of d'Artelia. CORE-LOC™ is a trademark of the United States Army Corps of Engineers. Xbloc® is a registered trademark of Delta Marine Consultants.

Sales Worldwide: +44 131 553 1380

Sales Americas: +1 407 735 2400

More Information: sales@codaoctopus.com salesamericas@codaoctopus.com www.codaoctopus.com

Technical Support Worldwide: +44 131 553 7003

Technical Support Americas: +1 888 340 2632