

**Lighter/Smaller/Reduced Cost  
Upgraded to the 4G Performance Engine  
More Accurate, More Dynamic, Easier to  
Integrate**

### Benefits

- Improved situational awareness
- Highest definition of multibeam data output in the world
- Real time decision making
- Increased productivity
- Maintain subsea operations in zero visibility
- Enhanced safety
- Expert 24x7 Technical Support



**250-4000m Depth Rating**

## The most advanced real time 3D sonar in the world.

**The Echoscope<sup>4G</sup>® is the latest of our fourth-generation real-time 3D imaging sonar platform. The Echoscope<sup>4G</sup> is lighter, smaller and uses less power than our third-generation systems. It deploys our 4G performance pack to include our new beamformer that supports industry standard 100mb ethernet capability, Ping Pong alternating ping mode, increased ping rate to 20Hz, and reduced range resolution to 2cm.**

The Echoscope<sup>4G</sup> offers two different models with three different depth ratings with a wide range of flexible applications:

- Dual Frequency (375/630kHz) Real-Time 3D imaging & mapping system
- XD Triple-Frequency (240/375/630kHz) Real-Time 3D imaging & mapping system

The Echoscope<sup>4G</sup> is the world's highest resolution real-time 3D sonar. Built around unique patented technology, it generates a complete 3D model, composed of over 16,000 soundings, from each and every acoustic transmission. This 3D model is entirely refreshed up to 20 times per second with each new transmission.

With sounding densities far in excess of those generated by other sonars, and with the new increased 20Hz ping rate, the Echoscope<sup>4G</sup> presents unrivaled clarity of dynamic operations and moving objects in video-like data format in low-visibility water conditions. All the Echoscope<sup>4G</sup> range take advantage of patented statistical rendering techniques to further enhance the clarity of the image, presenting the user with an intuitive and easy-to-interpret image.

When monitoring underwater activity, even when the target and the Echoscope are moving independently of each other, the 3D imagery remains clear and accurate, giving the viewer an instant three-dimensional understanding of the underwater environment.

In mapping and inspection tasks, the ping geometry of the Echoscope<sup>4G</sup> will allow a target to be visualized many times in a single pass, allowing a target to be viewed from many different angles. This allows complex subsea structures to be mapped with fewer shadows and a level of confidence and detail far beyond anything that can be achieved using alternative methods.

Whether deployed on inland waterway work or large scale offshore projects, the Echoscope<sup>4G</sup> real-time 3D sonar will provide clear, high definition imagery of the underwater environment.

### New Features

- Lighter/Smaller/Reduced Power/Lower Cost
- Latest 4<sup>th</sup> Generation Processing Engine
- Increased Ping Rate Now 20Hz
- Reduced Minimum Range Now 0.5m
- Ping Pong Alternating Ping Mode (e.g. alternating frequencies)
- Programmable TVG
- Standard 100Mb Ethernet for ROV/AUV applications



# Coda Octopus:3D

Real-Time Sonar Solutions

/Echoscope<sup>4G</sup>®

Technical Specifications		
Performance (by Model)	Dual Frequency	XD Triple Frequency
Frequency	375 and 630kHz software switchable	240/375 and 630kHz software selectable
Number of beams	128 x 128 (16,384 total)	128 x 128 (16,384 total)
Maximum range*	120m (394ft) at 375kHz 80m (262ft) at 630kHz	From 150m (492ft) at 240kHz 120m (394ft) at 375kHz 80m (262ft) at 630kHz
Minimum range*	0.5m (1.64ft)	0.5m (1.64ft)
Range resolution	2cm (0.8in)/ 3cm (1.2in)*	2cm (0.8in)/ 3cm (1.2in)*
Update rate (ping rate)	Up to 20 Hz software selectable	Up to 20 Hz software selectable
Angular coverage	50° x 50°, 24° x 24°	90° x 44°, 50° x 50°, 24° x 24°
Beam spacing	0.39° or 0.19°	0.70° to 0.19°
*The actual working range will depend on the target's size, reflectivity, and the level of detail required for the application		
Physical		
Dimensions (h x w x d) (excluding connectors and handles)	328mm x 300mm x 145mm (12.9in x 11.8in x 5.7in)	328mm x 300mm x 156mm (12.9in x 11.8in x 6.1in)
Weight in Air	20.6 kg (45.5 lbs)	21 kg (46.3 lbs)
Weight in Water	10.9 kg (24 lbs)	10.9 kg (24 lbs)
Power Consumption	3 - 6A at 24Vdc	3 - 6A at 24Vdc
Depth Rating	250m (820ft), 600m (1,968ft), 3,000m (9,840ft), with 4,000m (13,123ft) option*	250m (820ft), 600m (1,968ft), 3,000m (9,840ft), with 4,000m (13,123ft) option*
Interfaces		
Sonar head to PSU	Power: 24V DC Control: RS232 Serial Cable Data: 100Mb Industry Standard Ethernet Single cable for power, data, and control	Power: 24V DC Control: RS232 Serial Cable Data: 100Mb Industry Standard Ethernet Single cable for power, data, and control
Applications		
Port and harbor security, Infrastructure Inspection, Underwater construction, Dredging and rock dumping, Mattress laying, Cable laying, burial and pull-in monitoring, Scour inspection, Marine salvage, Diver monitoring and identification, Obstacle avoidance and ROV navigation, Decommissioning, Contraband detection, Biological study (fisheries, marine mammals)		
*Depending on operating mode		
**Available upon request		

## Echoscope® Features

- High definition 3D sonar image generated in real-time
- Mosaicking capability
- Displays complex moving structures accurately
- Accurate even in turbid water
- Accurate geo-referenced data
- Versatile DTM output options
- Very easy to use even by non sonar experts such as crane operators and law enforcement officers

Echoscope<sup>4G</sup>®, Echoscope®, CodaOctopus® (Reg, Us Pat & TM off) are trademarks of Coda Octopus.

The information in this publication was correct when it was published but specifications may change without notice. Photos are included for illustrative purposes only and actual items may differ in appearance. Coda Octopus does not assume responsibility for typographical or photographic errors. Issue 1.0 (1.19)

Sales Worldwide: +44 131 553 1380

Sales Americas: +1 863 937 8985

Sales Australasia: +61 894 308 045

More Information: sales@codaoctopus.com salesamericas@codaoctopus.com

www.codaoctopus.com

Technical Support Worldwide: +44 131 553 7003

Technical Support Americas: +1 888 340 2632

